



Easy Clip Line® – for bags

- For closure of bags and nets
- Firm, safe packaging
- Made of high-quality stainless steel and industrial plastic
- Horizontal version optionally available

Why clip with EZ 4500?

The clipping machine EZ 4500 of the Easy Clip Line® reliably closes bags and nets. In particular, it is used for efficient packaging of poultry. Numerous other products can be packaged in a tamper-proof manner in bags with the originality closure clip. Various machine designs are available for different product and bag sizes.



Advantages

- Firm, tight and hygienic packaging due to clip closure
- Automatic clip triggering by insertion of the tail into the slot of the clip guide
- Simple operation
- Integrated pneumatic knife for shortening the bag tail
- Table top or in-built version, left-hand or right-hand, with backward-inclined or upright machine on base plate
- Low air consumption
- Processes high-quality clips –

certified safe for use with food by SGS INSTITUT FRESENIUS

- Clip and loop manufacture certified in accordance with ISO 22000



Quality and hygiene

- Hygienic design made of stainless steel and industrial plastic for easy cleaning



Maintenance

- Low maintenance and low wear



owing to the small number of moving parts

+ Optional equipment

- Horizontal version
- Trolley for horizontal version
- Bracket for mounting on rod at diameters of 35 – 48 mm for horizontal version
- S-clips on spool for even more efficient production
- Pressure reducer with filter
- Machine feet (table top version)
- Labelling system EZ Tag-Feeder for tamper-proof product and origin labelling, as well as batch tracing



Tamper-proof labelling with the optional EZ Tag-Feeder labelling system

+ Combinability

MPL

Can be combined with the MPL poultry loader (bagger)

✓ Consumables

S-Clip: S 4524, S 4526, S 4528, S 4532

⏻ Function and operation

The clipping machine EZ 4500 operates pneumatically. By inserting the tail into the slot of the clip guide, the tail is shirred and the clipping process is triggered automatically. In parallel, the bag tail is cut with the pneumatic knife. Machines of the Easy Clip Line® can be adapted to suit each particular production condition. With the EZ Tag-Feeder labelling system a label can be provided with updated information during the packaging process and can be attached in a tamper-proof manner to the bag during clipping.

Technical data

Width	215 mm
Depth	503 mm
Height	826 mm
Weight	15 kg
Compressed air	5–7 bar / 0,5–0,7 MPa
Air consumption 5 bar	2.4 NL/cycle
Air consumption 7 bar	2.7 NL/cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.

