



Easy Clip Line® – plastic clip

- For closure of bags and nets
- Use with metal detectors
- Plastic clips in different colours
- Firm, safe packaging

Why clip with EZ P 700?

The clipping machine EZ P 700 of the Easy Clip Line® is the safe way to package poultry, bakery products, fruits, vegetables and many others in bags or nets. The nonmetal clip allows for an easy metal detection of the finished product. These plastic clips are available in different sizes and colours, and are furnished on spools.

✓ Advantages

- Plastic clips on spool
- Firm, uniform closure every time
- Automatic clip triggering by insertion of the tail into the slot of the clip guide
- Simple operation
- Integrated pneumatic knife for shortening the bag tail
- Table top or in-built version, left-hand or right-hand, with backward-inclined or upright machine on base plate
- Low air consumption
- Processes high-quality plastic

clips – certified safe for use with food by SGS INSTITUT FRESENIUS

- Clip and loop manufacture certified in accordance with ISO 22000

✓ Quality and hygiene

- Hygienic design made of stainless steel and industrial plastic for easy cleaning

✓ Maintenance

- Low maintenance and low wear



owing to the small number of moving parts

+ Optional equipment

- Horizontal version
- Trolley for horizontal version
- Bracket for mounting on rod at diameters of 35 – 48 mm for horizontal version
- Pressure reducer with filter
- Machine feet (table top version)



+ Combinability

MPL

Can be combined with the MPL poultry loader (bagger)

✓ Consumables

P-Clip: P 744

⏻ Function and operation

The clipping machine EZ P 700 operates pneumatically. By inserting the tail into the slot of the clip guide, the tail is shirred and the clipping process is triggered automatically. In parallel, the bag tail is cut with the pneumatic knife. Machines of the Easy Clip Line® can be adapted to suit each particular production condition. With the EZ Tag-Feeder labelling system a label can be provided with updated information during the packaging process and can be attached in a tamper-proof manner to the bag during clipping.

Technical data

Width	311 mm
Depth	467 mm
Height	758 mm
Weight	15 kg
Compressed air	5–7 bar / 0,5–0,7 MPa
Air consumption 5 bar	2.4 NL/cycle
Air consumption 7 bar	2.7 NL/cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.