

Why clip with EZ P 700?

The clipping machine EZ P 700 of the Easy Clip Line® is the safe way to package poultry, bakery products, fruits, vegetables and many others in bags or nets. The nonmetal clip allows for an easy metal detection of the finished product. These plastic clips are available in different sizes and colours, and are furnished on spools.

Easy Clip Line® - plastic clip

- For closure of bags and nets
- Use with metal detectors

- Plastic clips in different colours
- Firm, safe packaging



DETAILS



Advantages

- Plastic clips on spool
- Firm, uniform closure every time
- Automatic clip triggering by insertion of the tail into the slot of the clip guide
- $\, \bullet \,$ Integrated pneumatic knife for shortening the bag tail
- Table top or in-built version, left-hand or right-hand, with backward-inclined or upright machine on base plate
- Low air consumption
- Processes high-quality plastic clips certified safe for use with food by SGS INSTITUT FRESENIUS
- Clip and loop manufacture certified in accordance with ISO 22000

Quality and hygiene

 Hygienic design made of stainless steel and industrial plastic for easy cleaning



Maintenance

 Low maintenance and low wear owing to the small number of moving parts

Equipment options

- Horizontal version
- Trolley for horizontal version
- Bracket for mounting on rod at diameters of 35 to 48 mm for horizontal version
- Pressure reducer with filter
- Machine feet (table top version)
- Labelling system EZ Tag-Feeder for tamper-proof product and origin labelling, as well as batch tracing





Possible combinations

MPI

Can be combined with the MPL poultry loader (bagger)

Consumables

P-Clip: P 744

Function and operation

The clipping machine EZ P 700 operates pneumatically. By inserting the tail into the slot of the clip guide, the tail is shirred and the clipping process is triggered automatically. In parallel, the bag tail is cut with the pneumatic knife. Machines of the Easy Clip Line® can be adapted to suit each particular production condition. With the EZ Tag-Feeder labelling system a label can be provided with updated information during the packaging process and can be attached in a tamper-proof manner to the bag during clipping.

TECHNICAL DATA

Width

Depth

Height

Weight

311 mm

467 mm

758 mm

15 kg

Compressed air

5 - 7 bar / 0,5 - 0,7 MPa Air consumption 5 bar

2,4 NL/Cycle

Air consumption 7 bar

2,7 NL/Cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.

Excellence in Clipping

