



SC 600

Single-Clip Machine



Simply clipping

- For all plastic and natural casings, bags and nets
- Made of high-quality stainless steel and industrial plastic
- Upgrade to optional features at any time

Why clip with SC 600?

The SC 600 is ideally suited for closing pre-cut casings. It processes all casings from small diameters up to 90 mm. The modular system allows additional components to be easily fitted.



Advantages

- Pneumatically operated
- Service-friendly, easy exchange of die and cutting knife



Quality and hygiene

- Easy to clean due to smooth surfaces



Optional equipment

- Pressure reducer with filter
- Side tray with portioning stop

- Pneumatic knife (PM)
- Looper (GSE)



Function and operation

The single-clip machines are operated pneumatically. The closing of the gate gathers the casing before the clip is applied automatically. With the SCD machine the clip pressure can be adjusted via a click-stop scale individually and reproducibly. In addition, product specific closing speed and pressure can be set with the pressure regulator assembly.



Clip system solutions

The complete system of clipping machine, clips and loops from a single source ensures efficient and

Excellence in Clipping

poly-clip®
SYSTEM



SC 600

Single-Clip Machine



trouble-free production. Original clips from Poly-clip System guarantee the highest quality. Manufacturing is subject to the most rigorous quality controls. Certified in accordance with ISO 22000 and ISO 9001 they are designed to suit the production process perfectly. With its food-proof safety coating certified by the SGS INSTITUT FRESENIUS, Poly-clip SAFE-COAT technology ensures trouble-free production and if required a no-worry product warranty. Poly-clip System is the world's leading provider of clip system solutions.



Technical data

	Basis	GSE
Width	250 mm	275 mm
Depth	375 mm	570 mm
Height	915 mm	915 mm
Weight	16 kg	20 kg
Compressed air	5–7 bar / 0,5–0,7 MPa	5–7 bar / 0,5–0,7 MPa
Air consumption	1.8 NL/cycle	2.5 NL/cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.

SC_600_en_1152019_©Poly-clip_System Subject to technical modifications.

Poly-clip System GmbH & Co. KG

Niederdeckerstraße 1 • 65795 Hattersheim a. M. • Germany
Tel. +49 6190 8886-0 • contact@polyclip.de • www.polyclip.com

Excellence in Clipping

