

Why clip with SCA 6004?

The automatic single-clip machine SCA is particulary suited for portioning links of chubs (predominantly narrow beef/pork rounds and collagen casings) up to 46+ mm in diameter. Typical products are German Rindswurst, Speckwürste (Czech Republic and Slowakia), Austrian Knackers and Swiss Cervelats.

For beef sausage and knackwurst

- Fast, up to 300 cycles per minute in continuous mode
- S-clips on spool

- Low operating cost due to low air consumption
- Easy operation



DETAILS



Advantages

- Output up to 300 cycles per minnute in continuous mode
- Additional safety by two-handed triggering of first clip
- ein Betrieb ohne Darmbremse ist unmöglich
- Separate compressed air control of separator gate and clipping cylinder
- Easy to move due to trolley
- Stuffing horn (500 or 600 mm)
- Easy operation

Quality and hygiene

- All basic parts made of stainless steel
- Easy to clean due to smooth surfaces

Equipment options


- Linking arm (stainless steel) for connection of filler/clipping machine
- S-clips on spool for continuous production

Consumables

S-Clip: S 625, S 628



DETAILS



Function and operation

The clipping maschine SCA is connected and synchronized with a continuous filling machine via a linking arm and a control cable. The clipping impulse is generated by the filling machine. An electric/pneumatic control provides automatic operation. Due to the S-clips on spools continuous reloading is superfluous. One spool holds up to 10,500 clips.

Clip System Solutions

The complete system of clipping machine, clips and loops from a single source ensures efficient and trouble-free production. Original clips from Poly-clip System guarantee the highest quality. Manufacturing is subject to the most rigorous quality controls. Certified in accordance with ISO 22000 and ISO 9001 they are designed to suit the production process perfectly. With its food-proof safety coating certified by the SGS INSTITUT FRESENIUS, Poly-clip SAFE-COAT technology ensures trouble-free production and if required a no-worry product warranty. Poly-clip System is the world's leading provider of clip system solutions.

TECHNICAL DATA

Width

Depth

Height

Weight

320 mm

455 mm

900 mm

51 kg

Compressed air

Air consumption

4 - 5 bar /

0,4 - 0,5 MPa

1,7 NL/Cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.

Excellence in Clipping

