

## SCD 500

### Single-Clip Machine



#### Natural and protein casings

- Special version for thin natural casings
- Suitable for integration into hanging lines for natural and protein casings
- Made of high-quality stainless steel and industrial plastic

#### Why clip with SCD 500?

The SCD 500 has been specially designed for processing thin natural casings. It closes sheep casings, hog casings as well as small diameter beef rings and plastic casings totally securely.



#### Advantages

- Pneumatically operated
- Service-friendly, easy exchange of die and cutting knife



#### Quality and hygiene

- Easy to clean due to smooth surfaces



#### Optional equipment

- Pressure reducer with filter
- Side tray with portioning stop



#### Consumables

S-Clip: S 522, S 524, S 526, S 528, S 532  
Loops: GS 22



#### Function and operation

The single-clip machines are operated pneumatically. The closing of the gate gathers the casing before the clip is applied automatically. With the SCD machine the clip pressure can be adjusted via a click-stop scale individually and reproducibly. In addition, product



specific closing speed and pressure can be set with the pressure regulator assembly.

Excellence in Clipping

**poly-clip®**  
SYSTEM

## SCD 500

### Single-Clip Machine



#### Clip system solutions

The complete system of clipping machine, clips and loops from a single source ensures efficient and trouble-free production. Original clips from Poly-clip System guarantee the highest quality. Manufacturing is subject to the most rigorous quality controls. Certified in accordance with ISO 22000 and ISO 9001 they are designed to suit the production process perfectly. With its food-proof safety coating certified by the SGS INSTITUT FRESENIUS, Poly-clip SAFE-COAT technology ensures trouble-free production and if required a no-worry product warranty. Poly-clip System is the world's leading provider of clip system solutions.

#### Technical data

Width	250 mm
Depth	390 mm
Height	940 mm
Weight	12 kg
Compressed air	5–7 bar / 0,5–0,7 MPa
Air consumption	3.3 NL/cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.